



7. ☐ Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
- ☐ Computer Readable copy
  - ☐ Paper Copy (identical to computer copy)
  - ☐ Statement verifying identity of above copies
8. ☒ Assignment Papers
9. Power of Attorney
- ☒ Is attached.
  - ☐ The power of attorney appears in the original papers of the prior application.
  - ☐ Since the power does not appear in the original papers, a copy of the power in the prior application is enclosed.
10. ☐ Information Disclosure Statement (IDS)
- ☐ Copies of IDS Citations
11. Amendments
- ☐ A preliminary amendment is enclosed.
  - ☐ Cancel in this application claim(s) \_\_\_\_\_ before calculating the filing fee. At least one independent claim is retained for filing purposes.
  - ☐ Amend the specification by inserting before the first line the sentence: \_\_\_\_\_.
12. ☒ Return Receipt Postcard
13. Small Entity Status
- ☐ A small entity statement is enclosed.
  - ☐ A small entity statement was filed in the prior non-provisional application and such status is still proper and desired.
  - ☐ Is no longer claimed.
14. ☐ Priority of foreign application number \_\_\_\_\_, filed on \_\_\_\_\_ in \_\_\_\_\_ is claimed under 35 U.S.C. § 119(a)-(d)
15. ☐ Petition under 37 C.F.R. § 136 for Extension of Time
16. ☐ Other: \_\_\_\_\_

Address all future correspondence to:


Jeffrey C. Hood  
Conley, Rose, & Tayon, P.C.  
P.O. Box 398  
Austin, Texas 78767  
Phone: (512) 476-1400 Fax: (512) 703-1250

Signature

Name

Registration No.

Date



Jeffrey C. Hood


35,198

8/11/2000

PATENT  
5150-39300



"EXPRESS MAIL" MAILING LABEL  
NUMBER  
DATE OF DEPOSIT  
I HEREBY CERTIFY THAT THIS PAPER OR  
FEE IS BEING DEPOSITED WITH THE  
UNITED STATES POSTAL SERVICE  
"EXPRESS MAIL POST OFFICE TO  
ADDRESSEE" SERVICE UNDER 37 C.F.R. §  
1.10 ON THE DATE INDICATED ABOVE  
AND IS ADDRESSED TO THE ASSISTANT  
COMMISSIONER FOR PATENTS, BOX  
PATENT APPLICATION, WASHINGTON,  
D.C. 20231

  
Derrick Brown

System and Method for Transferring Data Over An External  
Transmission Medium

By:

David W. Madden  
Aljosa Vrancic

Atty. Dkt. No.: 5150-39300

Jeffrey C. Hood/MSW  
Conley, Rose & Tayon, P.C.  
P.O. Box 398  
Austin, TX 78767-0398  
Ph: (512) 476-1400

00T30" T503E360

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention

This invention relates to data communications and data delivery over  
5 communication media between a host computer and a device, such as in host computer-  
based data acquisition systems.

### 2. Description of the Related Art

In many applications it is necessary or desirable for a host computer system to  
10 communicate data with an external device. Various transmission media and protocols  
exist for enabling communication between a host computer system and an external  
device. Examples of these types of external transmission media include IEEE 1394, the  
Universal Serial Bus (USB), and other serial or parallel buses which enable packet-based  
communication. Also, a generic method to communicate data across multiple operating  
15 systems is desirable.

Typically, the host computer system includes communication logic for interfacing  
with the external communication line. For example, in a computer system which includes  
IEEE 1394 communication capabilities, the computer system includes an IEEE 1394  
interface for communication through the IEEE 1394 bus. The computer system also  
20 typically includes various layers of driver software which allow an application to  
interface with and use the IEEE 1394 bus for communicating with the external device.  
One problem that often arises with host computer driver software which is used to  
interface to an external communication medium is that the host software requires  
numerous context switches between user mode and kernel mode. As is well known in the  
25 art, a user mode/kernel mode transition requires a context switch by the CPU. This  
generally requires a large amount of CPU resources or cycles to make the context switch  
each time a user mode/kernel mode transition occurs. Therefore, it would be desirable to  
provide a host computer driver software implementation which is operable to

communicate with an external communication medium that minimizes user mode/kernel mode transitions.

Host computer software which interfaces to an external communication medium may also sustain passive/dispatch level transitions. Dispatch level is the highest level of software interrupt, just below hardware interrupts in priority. Passive/dispatch level transitions typically occur when a process running at dispatch level must wait for a response or for a resource to become available. Explicit 'waits' may not be performed at dispatch level, but must instead be performed at a passive level. For example, an interrupt routine handling non-page-locked memory must be executed at passive level because memory paging requires waiting. Similarly, synchronous communication (I/O) between a host computer and a 1394 device must be performed at passive level because the host computer must wait for responses from the 1394 device. Thus, a process running at dispatch level must transition to passive level to execute a task which entails an explicit wait. Also, many kernel functions are only meant to run at passive level. Therefore, between successive reads or writes, it is typically the case that a passive level routine requests a read/write operation. The Interrupt Service Routine (ISR) (running at dispatch) is dispatched upon completion of the transaction. The ISR copies data over, and signals to the passive level thread to continue with its next read/write.

These transitions also result in a large amount of overhead on the host CPU. In particular, dispatch/passive transitions may degrade performance by several orders of magnitude due to passive level context switching in preemptive multi-tasking kernel systems, such as Microsoft Corporation's Windows NT 2000. Therefore, a system and method is also desired for reducing the number of passive/dispatch level transitions in the communication process.

A problem that frequently occurs in multi-threaded operating systems is that threads used for communicating with the external communication medium may be required to operate in a particular mode, such as user or kernel mode at passive or dispatch level. The operating system may allocate multiple threads in different time slots. Thus, threads used for managing the external communication medium may be

interspersed with other threads that may be required to operate in a different mode, i.e., in a different user/kernel mode or at a different passive/dispatch level. This results in a large number of context switches by the CPU as the different threads are executed. Therefore, it would be desirable to provide a system which minimizes these types of context switches.

Another issue associated with host driver software related to external transmission media is the effort typically required to develop new drivers for particular buses and their related protocols. As is well known in the art, new driver software is generally written 'from scratch', because of the many dependencies of the software upon the operating system, the bus, and associated protocols. This approach requires significant resources in terms of both time and effort involved, and often impedes the rapid adoption and support of new transmission media and protocols. Therefore, an improved method and system for implementing driver software is desired.

## SUMMARY OF THE INVENTION

00T30"TS0E9S0

The present invention comprises various embodiments of a system and method for transferring data over an external transmission medium. A host computer may be coupled to a device, such as an instrument, which may be further coupled to a sensor. The instrument may be a data acquisition (DAQ) device, which combined with the sensor, may be operable to collect data concerning pressure, temperature, chemical content, current, resistance, voltage, audio or image data, or any other detectable attribute. The host computer may be operable to control the instrument by sending requests to read from or write to the instrument's memory registers. The host computer may be further operable to obtain data from the instrument for storage and analysis on the host computer system. In one embodiment, the host computer may comprise a computer system, wherein the computer system is coupled to the instrument through a serial bus, such as an IEEE 1394 bus, as described in an IEEE 1394 protocol specification. In other embodiments the bus may implement other protocols such as Ethernet, USB, TCP/IP, or any other serial or parallel communication protocol.

A transfer object may be configurable to encapsulate data transfer-related functionality to provide a generic interface for transmission of data over a variety of external transmission media and protocols. The transfer object may include transfer information including a transfer type specification describing the kind of data transfer of a particular transfer request, such as synchronous single-point read, synchronous single-point write, asynchronous single-point read, asynchronous single-point write, synchronous block read, synchronous block write, asynchronous block read, asynchronous block write, synchronous random read, asynchronous random read, 1394 asynchronous random read, and 1394 synchronous random read.

The transfer object may further include a request block object which may provide a generic operating system(OS)-independent and bus-independent interface encapsulating OS-dependent and protocol/bus-dependent data related to the transfer. The transfer object may also include various callback functions, such as a static callback function, an

intrinsic callback function, and an optional pointer to a user callback function, as well as a link to another transfer object, thus providing a mechanism whereby multiple transfer objects may be chained together sequentially. Finally, a toolbox may be included as part of the data transfer system, which may encapsulate inter-driver communication functions which may be accessed by the transfer object to navigate through layers of driver software between the application software and the bus hardware.

According to one embodiment of the present invention, a user application may request one or more transfer requests. Such transfer requests may originate with the application software and may be received by 1394 PAL-FW driver, such as National Instrument's NI-PAL F/W driver program, and may comprise a variety of requests to a remote device such as data reads, data writes, control requests, or any other type of data transfer related to remote device management or use.

Transfer objects corresponding to each of the plurality of data transfer requests may be built and linked together to form a sequential chain. The information required to execute each request may be included in the corresponding transfer object. The chain of transfer objects may then be submitted for execution by calling a perform request function on the first transfer object in the chain. The request of each transfer object in the chain may then be executed sequentially. If the current transfer object is the first transfer object in the chain, then the request of the current transfer object may be executed on a current thread at passive level or higher, in either user mode or kernel mode. If the current transfer object is not the first transfer object in the chain, the request of the current transfer object may be executed on a system (kernel) thread at dispatch level.

When a request is executed, the transfer object may execute functions from the toolbox to navigate through intervening software/driver layers, down to the hardware layer where the request may be sent over the bus to the remote device. When a response to the request comes back over the bus, the OS may use a new system thread at kernel-dispatch level to execute a static callback function of the transfer object to return control to the current transfer object. Then the current transfer object may execute an intrinsic callback function of the current transfer object on the system thread at kernel-dispatch



level to complete the transaction and set an event indicating completion of the request. The transaction may be completed by copying response information from a buffer into main memory, such as with a read.

5 The static callback function may determine whether there is a user callback function attached to the current transfer object. If so, the user callback function may be executed on the system thread at kernel-dispatch level. The user callback may log information, such as timing information, for profiling the request process.

10 If there are no further transfer objects in the chain the process is finished. If there is another transfer object in the chain then the request of that transfer object may be performed on the system thread at kernel-dispatch level, and the process may continue as described above until there are no more transfer objects to process.

15 In one embodiment, after the request of the first transfer object in the chain is performed on the current thread, the caller may call a wait function on the last transfer object, putting its thread into sleep mode. Later, when the last transfer object has completed its request, the last transfer object may execute its callback function to set an event (on the last system thread at kernel-dispatch level). The waiting thread which is in sleep mode (and at kernel-passive level) may then be awakened in response to the event, and continue processing.

20 By using the above process of creating transfer objects and chaining them together for execution, the transitions back and forth between passive and dispatch level thread execution for each of the transfer request executions may be reduced up to 10,000% or avoided, saving significant overhead costs in terms of CPU time and resources. If the series of requests is initiated in user mode (passive), rather than kernel mode (passive), the present invention may provide even greater benefits with respect to overhead as the  
25 corresponding user/kernel mode transitions may be avoided, given that user/kernel mode transitions are generally very expensive in terms of CPU cycles. Furthermore, the modular design of the transfer object which encapsulates the platform-dependent aspects of the data-transfer process makes it much easier to develop and maintain driver software for a variety of different platforms and buses/protocols.

## **BRIEF DESCRIPTION OF THE DRAWINGS**

Other advantages and details of the invention will become apparent upon reading the following detailed description and upon reference to the accompanying drawings in  
5 which:

Figure 1 illustrates a data acquisition system, according to one embodiment.

Figure 2A illustrates a 1394/PCI data acquisition system, according to one embodiment.

10 Figure 2B is a block diagram of a 1394/PCI data acquisition system, according to one embodiment.

Figure 3A is a block diagram of a 1394 data acquisition system, according to one embodiment.

15 Figure 3B is a block diagram of a 1394/PCI data acquisition system, according to another embodiment.

Figure 4 is a block diagram of the software architecture of the system, according to one embodiment.

Figures 5 is a block diagram of a transfer object, according to one embodiment.

20 Figures 5A is a diagram of transfer object transfer types, according to one embodiment.

Figures 6 is a flowchart of the request process, according to one embodiment.

Figure 7 is a flowchart of the transfer object creation process, according to one embodiment.

25 Figure 8 is a detailed flowchart of the request execution process, according to one embodiment.

While the invention is susceptible to various modifications and alternative forms, specific embodiments thereof are shown by way of example in the drawings and will herein be described in detail. It should be understood, however, that the drawings and

detailed description thereto are not intended to limit the invention to the particular form disclosed, but on the contrary, the intention is to cover all modifications, equivalents and alternatives falling within the spirit and scope of the present invention as defined by the appended claims.

5

007130-03100

## DETAILED DESCRIPTION OF THE EMBODIMENTS

### Incorporation by Reference

5 U.S. Patent No. 5,875,313 titled "PCI Bus to IEEE 1394 Bus Translator Employing Write Pipe-Lining and Sequential Write Combining", whose inventors are Glen O. Sescila III, Brian K. Odom, and Kevin L. Schultz, and which issued on February 23, 1999, is hereby incorporated by reference in its entirety as though fully and completely set forth herein.

### Figure 1 – A Data Acquisition System

10 Figure 1 illustrates a data acquisition system according to one embodiment. It is noted that the present invention may be used in various types of systems where a host computer communicates with an external device. Exemplary systems include test and measurement systems, industrial automation systems, process control systems, robotics systems and other types of systems. In the preferred embodiment described below, the device is a data acquisition (DAQ) device, and the system is a computer-based DAQ system.

15 As Figure 1 shows, a host computer system 108 may be coupled through a communication medium 220 to a data acquisition device or instrument 110 which may be further coupled to a sensor 112. In a preferred embodiment, the bus 220 may be an IEEE 1394 bus, such as described in the current or future IEEE 1394 protocol specifications, although in other embodiments the bus may implement other protocols such as Ethernet, USB, TCP/IP, or any other serial or parallel communication protocol. The following describes one embodiment of the present invention which uses the IEEE 1394 bus, although it is noted that the invention may be used with any of various communication media.

25 The sensor 112 may be any type of transducer which is operable to detect environmental conditions and send sensor data to the instrument 110. The instrument

110 may be a data acquisition (DAQ) device, which combined with the sensor 112, may be operable to collect data concerning pressure, temperature, chemical content, current, resistance, voltage, audio or image data, or any other detectable attribute. For example, the DAQ system may be an image acquisition system or a machine vision system. The instrument or DAQ device 110 may also include data generation capabilities. The host computer system 108 may be operable to control the instrument 110 by sending requests to read from or write to the instrument's memory registers. The host computer system 108 may be further operable to obtain data from the instrument 110 for storage and analysis on the host computer system 108, either by issuing read requests or by programming the instrument 110 to send data to the memory of the host computer 108.

The host computer 108 preferably includes a memory medium on which computer programs of the present invention may be stored. The host computer executes instructions from the memory medium to handle device retry requests on the communication medium 220. The memory medium may include a software architecture similar to that shown in Figure 4.

#### Figure 2A: A 1394/PCI Data Acquisition System

Figure 2A illustrates one embodiment of the data acquisition system 110. As shown in Figure 2A, host computer system 108 may be coupled to a PCI instrument 110A through serial bus 220, such as an IEEE 1394 bus.

In one embodiment, as shown in Figure 2A, the instrument 110A may include a PCI device 208 which may be coupled to a PCI/1394 translator 204 through a PCI bus 210. In one embodiment, the translator 204 may include a National Instruments FirePHLITM, which provides translation between the IEEE 1394 protocol and PCI, and error management, described below with reference to Figure 5. The host computer system 108 may be operable to communicate with the PCI device 208 through the 1394 bus 220 via the 1394/PCI translator 204. The 1394/PCI translator 204 may be operable to translate between the 1394 and PCI address spaces, allowing the host computer system 108 to send 1394 requests to and receive 1394 responses from the PCI device 208. The

1394/PCI translator thus allows existing PCI devices to be used in an IEEE 1394 system. For more information on the 1394/PCI translator 204, please see U.S. Patent No. 5,875,313 titled "PCI Bus to IEEE 1394 Bus Translator Employing Write Pipe-Lining and Sequential Write Combining", which was incorporated by reference above.

5

Figure 2B: A 1394/PCI Data Acquisition System

Figure 2B is a block diagram of the data acquisition system of Figure 2A, according to one embodiment. As Figure 2B shows, host 108 may be communicatively coupled to PCI instrument 208 through 1394 bus 220 and 1394/PCI translator 204, described above with reference to Figure 2A. Host 108 may be connected to the 1394 bus 220 via a 1394 interface 230.

Figure 3A: A 1394 Data Acquisition System

Figure 3A is a block diagram of a 1394 data acquisition system, according to one embodiment. As shown in Figure 3A, the host 108 may be communicatively coupled to a 1394-compliant instrument 110B through 1394 bus 220. Host 108 may be connected to the 1394 bus 220 via 1394 interface 230. In this embodiment, because the instrument 110B is compliant with the IEEE 1394 protocol, translator 204 is not required.

Figure 3B: Another 1394 Data Acquisition System

Figure 3B is a block diagram of a 1394 data acquisition system, according to another embodiment. In Figure 3B, a host computer system and two 1394-compliant instruments 110C and 110D may be coupled together via the 1394 bus 220. Each instrument 110 may be further coupled to a sensor 112 (A and B). In one embodiment, each instrument 110 may be configured with a processor card 324 with memory on board to execute driver software, a PCI instrument card 208 which may be operable to accept and manage sensor data from sensor 112, and a 1394/PCI bridge or translator 204, such as a National Instruments FirePHLITM, which provides translation between the IEEE 1394 protocol and PCI, and error management, described below with reference to Figures

5A and 5B. In some embodiments, the processor card 324 may include any of a variety of processors, such as a CPU, or a Field Programmable Gate Array (FPGA), as well as memory for storing programs and data. In one embodiment, the primary function of the host 108 is to configure the two instruments 110C and 110D for the bus 220 so that the two instruments 110C and 110D may communicate with each other as peers. Once the two instruments 110C and 110D are configured for the bus 220, the host 108 may no longer be needed for further operations, although it should be noted that the host 108 should not be disconnected because this may cause a bus reset, which would then require that the two instruments 110C and 110D be configured again.

#### Figure 4: Software Architecture

Figure 4 is a block diagram of the software architecture of the system, according to one embodiment. As Figure 4 shows, the top layer of the software architecture may be application software 402. The application software 402 may be any software program which may be operable to provide an interface for control and/or display of a data acquisition (DAQ) process. In one embodiment, the software application 402 may include a program developed in National Instrument's LabVIEW™ or LabWindows/CVI development environments. A driver program 404 may be below the application software 402. The driver 404 may be a DAQ driver 404, such as National Instrument's NI-DAQ driver program. The next software layer may optionally be a platform abstraction layer (PAL) driver 406, such as National Instrument's NI-PAL driver program. The PAL 406 may operate to abstract the internal communication bus and operating system to a common API. A 1394 platform abstraction layer firewire (PAL-FW) 1394 driver 408, such as National Instrument's NI-PAL F/W driver program, may be below the NI-PAL driver 406. This software preferably manages the data transmission process using transfer objects according to one embodiment of the present invention, described below with reference to Figures 5-8. A 1394D host interface 410 may be below the NI-PAL F/W driver 408, such as provided by Microsoft Corporation, which abstracts the 1394 chipset driver layer. The 1394D host interface 410 provides an

interface to 1394 chipset driver software, such as OHCI 1394 driver software, which interfaces with the relevant hardware; i.e., the 1394 interface hardware.

#### Figure 5: Transfer Object

5           Figure 5 is a block diagram of one embodiment of a transfer object. A transfer object may be configurable to encapsulate data transfer-related functionality to provide a generic interface for transmission of data over a variety of external transmission media and protocols. In the preferred embodiment, the NI-1394 driver 408 creates and uses transfer objects for improved data transfers on the bus 220. As Figure 5 shows, transfer  
10   object 502 may include transfer information 504, which may include a transfer type specification describing the kind of data transfer of a particular transfer request, described below with reference to Figure 5A.

          In one embodiment, the transfer object 502 may further include a request block object 506 which may provide a generic OS-independent and bus-independent interface  
15   encapsulating OS-dependent and protocol/bus-dependent data 508 related to the transfer. In one embodiment, the transfer object 502 may also include various callback functions, such as a static callback function 510 (common to all derived transfer objects), an intrinsic callback function 512, and an optional pointer to a user callback function 514, whose uses are described below with reference to Figures 7 and 8 below.

20           The transfer object 502 may also include a link 516 to another transfer object, thus providing a mechanism whereby multiple transfer objects may be chained together sequentially, a feature whose utility is also described below with reference to Figures 6-8.

          Finally, as can be seen in Figure 5, a toolbox 520 may be included as part of the data transfer system. The toolbox 520 may encapsulate inter-driver communication  
25   functions 522 which may be accessed by the transfer object 502 to navigate through layers of driver software between the application software and the bus hardware, as described with reference to Figure 4, above.

#### Figure 5A: Transfer Object Transfer Types



As mentioned above with reference to Figure 5, transfer information 504 may include a transfer type specification describing the kind of data transfer of a particular transfer request. Figure 5A shows a hierarchy of transfer types which may be included in a transfer object's transfer information. Transfer types may include asynchronous single-point read 540, synchronous single-point read 545, asynchronous single-point write 550, synchronous single-point write 555, asynchronous block read 560, synchronous block read 565, asynchronous block write 570, synchronous block write 575, asynchronous random read 580, synchronous random read 582, as well as 1394 asynchronous random read 584, and 1394 synchronous random read 586. Although not shown, in various embodiments, asynchronous random write, synchronous random write, 1394 asynchronous random write, and 1394 synchronous random write may be included in the transfer object transfer types.

The hierarchy shows one embodiment of an inheritance tree for transfer object classes. In one embodiment, generic transfer object class 501 is the root class from which the transfer type-specific transfer object classes may be derived. Specifically, the asynchronous transfer classes, such as asynchronous single-point read 540, asynchronous single-point write 550, asynchronous block read 560, asynchronous block write 570, asynchronous random read 580, and 1394 asynchronous random read 584 may be directly inherited from the transfer object class 501. As may be seen in Figure 5A, the synchronous transfer classes, such as synchronous single-point read 545, synchronous single-point write 555, synchronous block read 565, synchronous block write 575, synchronous random read 582, and 1394 synchronous random read 586, may be inherited from the corresponding asynchronous transfer classes, because the system typically operates in asynchronous mode, and synchronous mode generally requires all of the properties of the asynchronous mode plus one extra attribute: requiring a performRequest function of a transfer object to block until the transfer object's transaction is completed.

In one embodiment, asynchronous/synchronous reads and writes may refer to single point reads and writes, wherein each read or write transfers data to or from a single

memory address. In contrast, block reads and writes may refer to sequential reads or writes to or from memory which may be packaged together in one transfer object.

Random reads and writes may refer to multiple data reads and writes to scattered memory locations or offsets. In one embodiment, the system hardware, such as the 1394 bus or USB and related hardware, may be operable to perform random writes, such that a set of random data writes may be collected into one packet, which may improve performance as compared to sending each write in its own packet.

In one embodiment, the 1394 hardware, e.g., the translator 204, may not provide true random read capability, in which case 1394-specific random read transfer object sub-classes may be derived from the general random read transfer object classes, and provide special logic to handle the data transfer operation, as shown in Figure 5A.

#### Figure 6: Flowchart of the Request Process

Figure 6 is a high-level flowchart of the request process, according to one embodiment of the present invention. As Figure 6 shows, in 600 a user application 402 requests one or more transfer requests, then in 602 a plurality of data transfer requests may be received by the NI-1394 driver 408. Such transfer requests may originate with the application software 402 referenced in Figure 4, and may be received by 1394 PAL-FW driver 408, such as National Instrument's NI-PAL F/W driver program, also referenced in Figure 4. The transfer requests may comprise a variety of requests to a remote device or instrument, as described above with reference to Figures 2 and 3, such as data reads, data writes, control requests, or any other type of data transfer related to remote device management or use.

In 604, transfer objects corresponding to each of the plurality of data transfer requests may be built and linked together to form a sequential chain. The information required to execute each request may be included in the corresponding transfer object, as described above with reference to Figure 5, above. Further details of this build process are described with reference to Figure 7, below. In one embodiment, because the process may be asynchronous, steps 600-604 may occur in an iterative fashion, i.e., the user may

request more transfer requests before the chain of transfer requests is submitted in 606, in which case the transfer requests will be received, as indicated in 602, described above, and added to the chain of transfer objects, as indicated in 604. This loop may continue until either a flush occurs or until a buffer is full, at which time 606, described below, may be executed.

In 606, the chain of transfer objects may be submitted for execution. In one embodiment of the invention, the submission may be effected by calling a perform request function on the first transfer object in the chain.

In 608, the request of each transfer object in the chain may be executed sequentially, the details of which are described with reference to Figure 8, below.

#### Figure 7: Flowchart of the Transfer Object Chain Creation Process

Figure 7 is a flowchart of one embodiment of the transfer object chain creation process performed in step 604, of Figure 6 above. As shown in Figure 7, in 702 memory may be allocated for a transfer object itself. In 704 memory may be allocated for the component data structures of the transfer object, and initialized with transfer information. In one embodiment, the transfer information for each transfer object may include a transfer type, as well as the data to be transferred. As mentioned above, transfer types may include synchronous single-point read, synchronous single-point write, asynchronous single-point read, asynchronous single-point write, synchronous block read, synchronous block write, asynchronous block read, and asynchronous block write, as well as random read and random write.

In 706, OS-dependent and bus-dependent request structures for the transfer object may be built. In one embodiment, these structures may comprise the request block object mentioned above with reference to Figure 5, which may provide a generic OS-independent and bus-independent interface encapsulating OS-dependent and protocol/bus-dependent data related to a particular transfer. By encapsulating the platform-dependent data in this way, the interactions with the OS and the particular bus

used for the transfer may be abstracted, which may simplify both development and use of the system.

In 708, a user callback function may optionally be attached to the transfer object. The user callback function is preferably a user-defined function associated with a particular transfer object which may be operable to execute a task after the transfer object's request has been executed, such as reporting timing data for execution analysis or profiling.

In 710 the transfer objects may be chained together through the use of the link 516 on each transfer object 502 (except the last), described with reference to Figure 5 above.

Thus the link of each transfer object (except the last) may be configured with a pointer or address to the next transfer object in the chain. In one embodiment, chaining the transfer objects together allows the sequential execution of a plurality of transfer requests while avoiding many of the mode and/or level transitions normally associated with multiple request executions. This issue is described in more detail below with reference to Figure 8. As shown in Figure 7, the process described above may be repeated until all transfer objects have been built and chained together.

#### Figure 8: Detailed Flowchart of the Request Execution Process

Figure 8 is a detailed flowchart of the request execution process, according to one embodiment. More specifically, Figure 8 is a detailed flowchart of 608, as referenced with respect to Figure 6, above. In one embodiment, the process may be launched by calling a perform request function on a first transfer object in the chain of transfer objects described with reference to Figures 6 and 7. Note that it is assumed that an OS under which the process is implemented supports multi-threading.

In 800, a distinction may be made between executing the request of the first transfer object in the chain of transfer objects and executing the request of any of the remainder of transfer objects in the chain. If the current transfer object is the first transfer object in the chain, then in 802, the request of the current transfer object may be executed on a current thread at passive level. In one embodiment, the current thread may execute

in user mode at passive level, e.g. if the thread is executing application software. In another embodiment, the current thread may run in kernel mode at passive level, such as when executing driver software. If, on the other hand, the current transfer object is not the first transfer object in the chain, then in 804, the request of the current transfer object may be executed on a system (kernel) thread at dispatch level.

In one embodiment, when a request is executed, the transfer object may execute functions from the toolbox 520, referenced with respect to Figure 5 above, to navigate through intervening software/driver layers, referenced in Figure 4, down to the hardware layer where the request may be sent over the bus to the remote device. When a response to the request comes back over the bus, then in 806 the OS may use a new system thread at kernel-dispatch level to execute a static callback function 510 of the current transfer object to return control to the current transfer object.

Then, in 808 the current transfer object may execute an intrinsic callback function 512 of the current transfer object on the system thread at kernel-dispatch level to complete the transaction and set an event indicating completion of the request. In one embodiment, the transaction may be completed by copying response information from a buffer into main memory, such as with a read.

In 812, the static callback function may determine whether there is a user callback function attached to the current transfer object, as described in 708 of Figure 7, above. If there is a user callback function attached, then in 814 the user callback function may be executed on the system thread at kernel-dispatch level. As mentioned above in 708 with reference to Figure 7, the user callback function of a transfer object may be a user-defined function which may be optionally attached to a transfer object during creation, and may be used to execute any task which the user wishes to be done after a particular request has completed. In one embodiment, the user callback may log information, such as timing information, for profiling the request process.

Finally, in 816, if there is another transfer object in the chain then the request of that transfer object may be performed on the system thread at kernel-dispatch level, as indicated in 804, and the process may continue as described above until there are no more

transfer objects to process. If there are no further transfer objects in the chain the process is finished.

In multithreaded applications, it is common to divide work among multiple threads. In such cases, one thread might wait for another thread to reach a particular state before proceeding. Some operating systems which support multi-threading provide event objects for thread synchronization. One thread may call a wait function, thus blocking its execution until a certain condition is satisfied. The other thread, after satisfying the condition, may notify the waiting thread by setting an event. In one embodiment, after the request of the first transfer object in the chain is performed on the current thread, as described with reference to 802, the last transfer object in the chain may call a wait function on the thread, putting it into sleep mode. Later, when the last transfer object has completed its request, the last transfer object may execute its callback function to set an event (on the last system thread at kernel-dispatch level), as in 814. The waiting thread which is in sleep mode may then be awakened in response to the event, and continue processing.

As will be clear to one skilled in the art, by using the above process of creating transfer objects and chaining them together for execution, the transitions back and forth between passive and dispatch level thread execution for each of the transfer request executions may be reduced or avoided, saving significant overhead costs in terms of CPU time and resources. If the series of requests is initiated in user mode (passive), rather than kernel mode (passive), then in some embodiments, the present invention may provide even greater benefits with respect to overhead as the corresponding user/kernel mode transitions may be avoided, given that user/kernel mode transitions are generally very expensive in terms of CPU cycles.

Furthermore, the modular design of the transfer object, which encapsulates the platform-dependent aspects of the data-transfer process, makes it much easier to develop and maintain driver software for a variety of platforms and buses/protocols, in that the developer need only supply a customized request block object and the appropriate



**WHAT IS CLAIMED IS:**

1. A method for transferring data over an external transmission medium, the method comprising:

- 5 receiving a plurality of transfer requests;  
building a chain of transfer objects, wherein each transfer object corresponds to one of the plurality of transfer requests; and  
performing the request of each transform object in the chain of transfer objects sequentially.

10

2. The method of claim 1, wherein the building the chain of transfer objects comprises:

- creating a plurality of transfer objects;  
attaching a user callback function to zero or more of the plurality of transfer  
15 objects; and  
linking the plurality of transfer objects together sequentially.

3. The method of claim 2, wherein said creating the plurality of transfer objects comprises:

- 20 allocating memory for each of the plurality of transfer objects;  
populating each of the plurality of transfer objects with transfer information, wherein the transfer information comprises one or more transfer types;  
allocating memory for a plurality of request block objects, wherein each of the plurality of request block objects corresponds to one of the plurality of transfer objects,  
25 wherein each of the request block objects is comprised in a corresponding one of the transfer objects, and wherein each of the request block objects provides an operating system-independent and bus-independent interface which encapsulates operating system-dependent and bus-dependent data; and



populating each of the plurality of request blocks with operating system-dependent and bus-dependent information related to a request of a corresponding transfer object.

5           4.     The method of claim 3, wherein the one or more transfer types comprise one or more of a read transfer, a write transfer, a single point transfer, a block transfer, a synchronous transfer, an asynchronous transfer, a random read transfer, or a random write transfer.

10           5.     The method of claim 1, wherein the performing the request of each transform object in the chain of transfer objects sequentially reduces passive/dispatch level transitions.

15           6.     The method of claim 1, wherein the performing the request of each transform object in the chain of transfer objects sequentially reduces user/kernel mode transitions.

20           7.     The method of claim 1, wherein the performing the request of each transform object in the chain of transfer objects sequentially comprises performing a request of a current transfer object;

              wherein said performing the request of the current transfer object is executed on a first thread at passive level if the current transfer object is the first transfer object in the chain; and

25                wherein said performing the request of the current transfer object is executed on a system thread at kernel-dispatch level if the current transfer object is not the first transfer object in the chain.

              8.     The method of claim 7, wherein the performing the request of the current transform object further comprises:

executing a static callback function to return control to the current transfer object on the system thread at kernel dispatch level;

executing a first callback function of the current transfer object to complete the request on the system thread at kernel dispatch level;

5        executing the first callback function of the current transfer object to set an event on the system thread at kernel dispatch level, wherein the event signals completion of the request;

determining if there is a user callback function attached to the current transfer object; and

10        executing the user callback function on the system thread at kernel dispatch level if there is a user callback function attached to the current transfer object.

9.       The method of claim 8,

15        wherein said performing the request of the first transfer object on the first thread at passive level comprises performing the request of the first transfer object on the first thread at kernel-passive level.

10.      The method of claim 8,

20        wherein said performing the request of the first transfer object on the first thread at passive level comprises performing the request of the first transfer object on the first thread at user-passive level.

11.      The method of claim 8, further comprising:

25        a last transfer object in the chain calling a wait function on the first thread after the performing the request of the first transfer object in the chain of transfer objects, wherein the calling the wait function on the first thread puts the first thread into a sleep mode;

wherein the first thread is awakened from the sleep mode in response to d) the current transfer object setting an event on the system thread at kernel dispatch level, wherein the event signals completion of the request; and

wherein the current transfer object is the last transfer object in the chain;

5

12. The method of claim 1,

wherein said external transmission medium comprises an IEEE 1394 bus, wherein said IEEE 1394 bus is implemented in accordance with an IEEE 1394 protocol specification.

10

13. The method of claim 1,

wherein said external transmission medium comprises a Universal Serial Bus (USB) bus.

15

14. The method of claim 1,

wherein said external transmission medium uses the Ethernet protocol.

15. A system for transferring data, the system comprising:

a host system including a processor and memory, wherein the memory stores data and driver software, and wherein the processor is operable to execute the driver software; an external communications medium; and

20

a device, wherein the device is coupled to the host system through the external transmission medium;

wherein the driver software is executable to receive a plurality of transfer requests, build a chain of transfer objects, and submit the chain of transfer objects for execution by the host system;

25

wherein each of the plurality of transfer objects corresponds to one of the plurality of transfer requests, and wherein each of the transfer objects is operable to perform a request to read from or write to the device; and

wherein the host system is operable to perform the request of each transfer object in the chain of transfer objects sequentially, wherein the request of the first transfer object in the chain of transfer objects is executed on a thread at passive level, and wherein the requests of subsequent transfer objects in the chain of transfer objects are executed on one or more system threads at kernel-dispatch level.

16. The system of claim 15,

wherein each of the plurality of transfer objects comprises:

transfer information, wherein the transfer information includes one or more transfer types;

a request block object, wherein the request block object provides an operating system-independent and bus-independent interface which encapsulates operating system-dependent and bus-dependent data related to a request of a corresponding transfer object, and wherein the request block object implements the external communications medium protocol in an operating system specific data structure;

a link which is operable to provide access to another transfer object;

an intrinsic callback function; and

a static callback function;

17. The system of claim 16,

wherein one or more of the plurality of transfer objects each further comprises a user callback function.

18. The system of claim 15,

wherein the software being executable to build a chain of transfer objects includes the software being executable to:

allocate memory for each of the plurality of transfer objects;

populate each of the plurality of transfer objects with transfer information which comprises one or more transfer types;

allocate memory for a plurality of request blocks, wherein each of the plurality of request blocks corresponds to one of the plurality of transfer objects, and wherein each of the request blocks is comprised in a corresponding one of the transfer objects, wherein each of the request block objects provides an operating system- and bus-independent interface which encapsulates operating system- and bus-dependent data;

populate each of the plurality of request blocks with operating system- and bus-dependent information relating to the request of the transfer object;

attach a user callback function to zero or more of the plurality of transfer objects;

and

chain the plurality of transfer objects together sequentially.

19. The system of claim 15,

wherein the host system being operable to perform the request of each transform object in the chain of transfer objects sequentially comprises the host system being operable to perform a request of a current transfer object on a first thread at passive level if the current transfer object is the first transfer object in the chain; and perform the request of the current transfer object on a system thread at kernel-dispatch level if the current transfer object is not the first transfer object in the chain.

20. The system of claim 19, wherein the host system being operable to perform the request of the current transfer object further comprises the host system being operable to:

execute a static callback function to return control to the current transfer object on the system thread at kernel dispatch level;

execute the intrinsic callback function of the current transfer object to complete the request on the system thread at kernel dispatch level;

execute the intrinsic callback function of the current transfer object to set an event on the system thread at kernel dispatch level, wherein the event signals completion of the request;

determine if there is a user callback function attached to the current transfer object;

execute the user callback function of the current transfer object on the system thread at kernel dispatch level if there is a user callback function attached to the current transfer object; and

21. The system of claim 19,

wherein the host system being operable to perform the request of the first transfer object on the first thread at passive level comprises the host system being operable to perform the request of the first transfer object on the first thread at kernel-passive level.

22. The system of claim 19,

wherein the host system being operable to perform the request of the first transfer object on the first thread at passive level comprises the host system being operable to perform the request of the first transfer object on the first thread at user-passive level.

23. The system of claim 19,

wherein the host system is further operable to execute a wait function of a last transfer object in the chain on the first thread after the performing the request of the first transfer object in the chain of transfer objects, wherein the executing the wait function of the last transfer object in the chain on the first thread puts the first thread into a sleep mode; and

wherein the first thread is awakened from the sleep mode in response to d) executing the intrinsic callback function of the current transfer object to set an event on the system thread at kernel dispatch level, wherein the event signals completion of the request, and wherein the current transfer object is the last transfer object in the chain.

24. The system of claim 15,

wherein the host system comprises a computer system.

25. The system of claim 15, wherein the one or more transfer types comprise one or more of a read transfer, a write transfer, a single point transfer, a block transfer, a synchronous transfer, an asynchronous transfer, a random read transfer, or a random write transfer.

26. The system of claim 15,  
wherein said external transmission medium comprises an IEEE 1394 bus, and  
wherein said IEEE 1394 bus is implemented in accordance with an IEEE 1394 protocol specification.

27. The system of claim 15,  
wherein said external transmission medium comprises a Universal Serial Bus (USB) bus.

28. The system of claim 15,  
wherein said external transmission medium uses the Ethernet protocol.

29. The system of claim 15,  
wherein the driver software comprises data acquisition driver software, and  
wherein the device comprises a data acquisition device.

30. The system of claim 15, further comprising a toolbox stored in the memory of the host computer, wherein the toolbox is operable to provide a generic interface to manage communications between drivers.

31. A transfer object, wherein the transfer object is configurable to encapsulate data transfer-related functionality to provide a generic interface for transmission of data over a variety of external transmission media and protocols, comprising:

transfer information, wherein the transfer information includes one or more transfer types;

a request block object, wherein the request block object provides an operating system-independent and bus-independent interface which encapsulates operating system-dependent and bus-dependent data related to a data transfer request, and  
5 wherein the request block object implements the external transmission medium protocol in an operating system specific data structure;

a link which is operable to provide access to another transfer object, wherein the link provides a mechanism for chaining transfer objects together;

10 an intrinsic callback function which is operable to execute a transaction to complete the data transfer request, and which is further operable to set an event signaling completion of the data transfer request; and

a static callback function;

15 32. The transfer object of claim 31, further comprising:

a user callback function, wherein the user callback function is operable to execute a user-specified task after the data transfer request of the transfer object has been executed.

20 33. The transfer object of claim 31, wherein the one or more transfer types comprise one or more of a read transfer, a write transfer, a single point transfer, a block transfer, a synchronous transfer, an asynchronous transfer, a random read transfer, or a random write transfer.



ABSTRACT OF THE DISCLOSURE

A system and method for transferring data over an external transmission medium. A host computer is coupled to a device through a serial bus, such as an IEEE 1394 bus.

5 A transfer object is configurable to encapsulate data transfer-related functionality, providing a generic interface for transmission of data over a variety of external transmission media and protocols. The transfer object includes transfer information describing the kind of data transfer of a particular request, a request block object which encapsulates OS- and protocol/bus-dependent data related to the transfer, various callback

10 functions, and a link to another transfer object for chaining transfer objects together sequentially. A toolbox encapsulating inter-driver communication functions is accessed by the transfer object to navigate through layers of driver software between the application and bus hardware. A user makes one or more transfer requests. Transfer objects corresponding to each request are built and linked together to form a sequential

15 chain. The requests of the transfer objects are executed sequentially. If the current transfer object is the first in the chain, the request is executed on a current thread at passive level or higher, otherwise the request is executed on a system (kernel) thread at dispatch level. When a response to the request returns, control is returned to the current transfer object. The current transfer object may execute a callback function to complete

20 the transaction and set an event indicating completion of the request. A user callback function may be executed. The process is repeated until all transfer objects are processed.




Figure 1




Figure 2A




Figure 2B






Figure 3B

a) Eigenschaften	
1) Eigenschaften	2) Eigenschaften
3) Eigenschaften	4) Eigenschaften
5) Eigenschaften	6) Eigenschaften
7) Eigenschaften	8) Eigenschaften
9) Eigenschaften	10) Eigenschaften
11) Eigenschaften	12) Eigenschaften
13) Eigenschaften	14) Eigenschaften
15) Eigenschaften	16) Eigenschaften
17) Eigenschaften	18) Eigenschaften
19) Eigenschaften	20) Eigenschaften
21) Eigenschaften	22) Eigenschaften
23) Eigenschaften	24) Eigenschaften
25) Eigenschaften	26) Eigenschaften
27) Eigenschaften	28) Eigenschaften
29) Eigenschaften	30) Eigenschaften
31) Eigenschaften	32) Eigenschaften
33) Eigenschaften	34) Eigenschaften
35) Eigenschaften	36) Eigenschaften
37) Eigenschaften	38) Eigenschaften
39) Eigenschaften	40) Eigenschaften
41) Eigenschaften	42) Eigenschaften
43) Eigenschaften	44) Eigenschaften
45) Eigenschaften	46) Eigenschaften
47) Eigenschaften	48) Eigenschaften
49) Eigenschaften	50) Eigenschaften
51) Eigenschaften	52) Eigenschaften
53) Eigenschaften	54) Eigenschaften
55) Eigenschaften	56) Eigenschaften
57) Eigenschaften	58) Eigenschaften
59) Eigenschaften	60) Eigenschaften
61) Eigenschaften	62) Eigenschaften
63) Eigenschaften	64) Eigenschaften
65) Eigenschaften	66) Eigenschaften
67) Eigenschaften	68) Eigenschaften
69) Eigenschaften	70) Eigenschaften
71) Eigenschaften	72) Eigenschaften
73) Eigenschaften	74) Eigenschaften
75) Eigenschaften	76) Eigenschaften
77) Eigenschaften	78) Eigenschaften
79) Eigenschaften	80) Eigenschaften
81) Eigenschaften	82) Eigenschaften
83) Eigenschaften	84) Eigenschaften
85) Eigenschaften	86) Eigenschaften
87) Eigenschaften	88) Eigenschaften
89) Eigenschaften	90) Eigenschaften
91) Eigenschaften	92) Eigenschaften
93) Eigenschaften	94) Eigenschaften
95) Eigenschaften	96) Eigenschaften
97) Eigenschaften	98) Eigenschaften
99) Eigenschaften	100) Eigenschaften




Figure 4




Figure 5






Figure 5A

```
graph TD; 600[User Requests Transfer Requests 600] --> 602[Receive One Or More Transfer Requests 602]; 602 --> 604[Build Chain of Transfer Objects Corresponding to Transfer Requests 604]; 604 --> 606[Submit Chain of Transfer Objects 606]; 606 --> 608[Execute Each Transfer Object Request 608]; 604 --> 600;
```

### Figure 6




Figure 7




Figure 8

**DECLARATION AND POWER OF ATTORNEY**

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled "SYSTEM AND METHOD FOR TRANSFERRING DATA OVER AN EXTERNAL TRANSMISSION MEDIUM," the specification of which:

- ☒ is attached hereto.  
☐ was filed on \_\_\_\_\_ as Application Serial No. \_\_\_\_\_  
 and was amended on \_\_\_\_\_ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose to the Patent and Trademark Office all information known to me to be material to patentability of the subject matter claimed in this application, as "materiality" is defined in 37 C.F.R. § 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate listed below, or under § 365(a) of any PCT international application listed below designating least one country other than the United States of America, and have identified below any foreign application for patent or inventor's certificate, or of any PCT international application, having a filing date before that of the application on which priority is claimed.

<u>Prior Foreign Application No.</u>	<u>Country</u>	<u>Filing Date</u> <u>(mm/dd/yy)</u>	<u>Priority</u> <u>Claimed</u>	<u>Cert. copy</u> <u>Attached</u>
N/A				

I hereby claim the benefit under 35 U.S.C. § 119(e) of any United States provisional application(s) listed below.

<u>Provisional Application No.</u>	<u>Filing Date</u> <u>(mm/dd/yy)</u>
N/A	

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s) listed below, or under § 365(c) of any PCT international application listed below designating the United States of America, and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose all information known to me to be material to the patentability of the subject matter claimed in this application, as "materiality" is defined in 37 C.F.R. § 1.56, which became available between the filing date of the prior application and the national or PCT international filing date of this application.

<u>Parent Application No.</u>	<u>Filing Date</u> <u>(mm/dd/yy)</u>	<u>Parent Patent No. (if applicable) or Status</u>
N/A		

The Assignee hereby revokes any previous Powers of Attorney and appoints Jeffrey C. Hood, Reg. No. 35,198, Kevin L. Daffer, Reg. No. 34,146, B. Noël Kivlin, Reg. No. 33,929, Eric B. Meyertons, Reg. No. 34,876 and David A. Rose, Reg. No. 26,223, each said attorneys being members or associates of the firm of Conley, Rose & Tayon, P.C., as attorney or agent for so long as they remain with such company or firm, with full power of substitution and revocation, to prosecute the application, to make alterations and amendments therein, to transact all business in the Patent and Trademark Office in connection therewith, and to receive the Letters Patent.

Please direct all communications to:

Jeffrey C. Hood  
Conley, Rose & Tayon, P.C.  
P.O. Box 398  
Austin, Texas 78767-0398  
Phone: (512) 476-1400

I hereby declare that all statements made herein of my own knowledge are true and that all statements made herein on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. § 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Inventor's Full Name: David W. Madden

Inventor's Signature:  Date: 8/10/2000

City and State (or Foreign Country) of Residence: Austin, TX Citizenship: USA

Post Office and Residence Address: 14709 Bessett Dr., Austin, TX, 78728  
(Include number, street name, city, state and zip code)

Inventor's Full Name: Aljosa Vrancic

Inventor's Signature:  Date: 8/10/2000

City and State (or Foreign Country) of Residence: AUSTIN, TX Citizenship: CROATIA

Post Office and Residence Address: 12349 METRIC BLVD #1613, AUSTIN TX, 78758  
(Include number, street name, city, state and zip code)